

HARNES, DICKEY & PIERCE, P.L.C.

Attorneys and Counselors
5445 Corporate Drive, Suite 400
Troy, Michigan 48098-2683
Phone: 248-641-1600
Fax: 248-641-0270
St. Louis, MO • Washington, D.C.

**RECEIVED
CENTRAL FAX CENTER**

NOV 15 2004

DATE: November 15, 2004

NO. OF PAGES (INCLUDING THIS PAGE):

6

FOR: Examiner Garland - Art Unit 2125

COMPANY: USPTO - Randolph Bldg.

FAX NO.: (703) 872-9306

PHONE:

ORIGINAL WILL FOLLOW BY:

- ☐ REGULAR MAIL
☐ OVERNIGHT MAIL
☐ COURIER
☒ WILL NOT FOLLOW

FROM: Monte L. Falcoff

Please let us know by phone or fax if you do not receive any of these pages.

COMMENTS:

The attached proposed amendment is for a personal interview on Tuesday, 11/16/04.

BEST AVAILABLE COPY

***** NOTICE *****

The information contained in this telefax transmission is intended only for the individual to whom or entity to which it is addressed. It may also contain privileged, confidential, attorney work product or trade secret information which is protected by law. If the reader of this message is not the intended recipient, or an employee or agent responsible for delivering the message to the addressee, the reader is hereby notified that any dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please immediately notify us by telephone and return the original message to us at the address above via the U.S. Postal Service. We will reimburse you for any reasonable expense (including postage) for the return of the original message.

11/16/04 PROPOSED AMENDMENT
USSN 10/791,403
0275M-000260/DVD

1. (currently amended) A method of manufacturing a joint by operating a riveting system having a riveting tool, a self-piercing rivet, and automotive vehicle panels, the riveting tool including an electric motor and a rivet punch, the method comprising:

(a) determining if the self-piercing rivet is located in the riveting tool;
(b) moving the self-piercing rivet to the riveting tool if step (a) is negative;

(c) energizing the electric motor to advance the self-piercing rivet;
(d) rotating a portion of the electric motor in response to step (c);
(e) converting the rotation of step (d) to linear displacement of the rivet punch;

(f) the rivet punch pushing against a solid head of the self-piercing rivet during insertion into the automotive vehicle panels;

(g) advancing the self-piercing rivet into an unpierced portion of the automotive vehicle panels, in response to step (e), without fluid actuation in the riveting tool;

(h) ~~[(g)]~~ outwardly diverging a leading end of the self-piercing rivet during insertion of the self-piercing rivet into the automotive vehicle panels;

(i)[(h)] preventing the self-piercing rivet from completely piercing through a die side one of the automotive vehicle panels; and

(i)[(i)] determining displacement associated with the rivet punch as a function of actuation speed used to insert the self-piercing rivet.

5. (currently amended) The method of claim 1 further comprising comparing [the] real-time sensed displacement associated with the rivet punch to prestored displacement values.

7. (currently amended) A method of manufacturing a joint by operating a riveting system having a riveting tool, a C-frame, a die, a self-piercing rivet, and automotive vehicle panels, the riveting tool including an electric motor and a rivet punch, the method comprising:

(a) robotically moving the C-frame to align a joint area of the automotive vehicle panels between the rivet punch and the die;

(b) inserting a self-piercing rivet to the riveting tool;

(c) rotating a portion of the electric motor;

(d) linearly moving the rivet punch in a fluid-free manner;

(e) clamping the automotive vehicle panels together in an area substantially surrounding the joint area;

(f)[(e)] punching the self-piercing rivet into a solid portion of the automotive vehicle panels;

(g) using the die to outwardly diverge a leading end of the self-piercing rivet during insertion of the self-piercing rivet into the automotive vehicle panels, always keeping the rivet punch and die coaxially aligned during use of the riveting tool;

(h) preventing the self-piercing rivet from completely piercing through a die side one of the automotive vehicle panels; and

(i) sensing real-time velocity of a component coupled to at least one of: the electric motor and the rivet punch.

13. (currently amended) A method of manufacturing by operating a riveting system including an electric motor, a belt, a transmission, a punch, a die, a workpiece clamp, a C-frame, and a self-piercing rivet, the method comprising:

- (a) stationarily attaching the die to the C-frame;
- (b) sensing if the self-piercing rivet has been fed adjacent to the punch;
- (c) rotating a portion of the electric motor;
- (d) rotating the belt in response to rotation of the electric motor;
- (e) rotating a portion of the transmission in response to rotation of the belt;
- (f) linearly displacing the punch in response to rotation of the portion of the transmission;
- (g) linearly advancing the workpiece clamp;

(h) using the punch to directly contact against and linearly push a solid head of the self-piercing rivet;

(i) using the die to outwardly diverge a leading end of the self-piercing rivet while preventing the self-piercing rivet from contacting directly against the die, always keeping the rivet punch and die coaxially aligned during use of the riveting tool;

(i) sending a signal between a computer controller and a sensor, and the sensor sensing a characteristic associated with the electric motor; and

(k)[(i)] electronically comparing a sensed and real-time action associated with operation of at least one of: the electric motor, the transmission, and the punch, to at least one pre-programmed value.

15. (original) The method of claim 13 further comprising clamping a pair of aluminum, automotive vehicle panels together in an area substantially surrounding the riveting area.

16. (original) The method of claim 13 further comprising inserting the self-piercing rivet into an unpierced area of automotive vehicle panels to be joined.

21. (new) A method of manufacturing attached automotive vehicle workpieces with a riveting tool, a frame, a die, and a self-piercing rivet, the method comprising:

- (a) robotically moving the frame to align a joint area of the automotive vehicle panels between a rivet punch of the riveting tool and the die, the rivet punch and die always being coaxially aligned during use of the riveting tool;
- (b) supplying the self-piercing rivet to the riveting tool;
- (c) rotating a portion of an electric motor of the riveting tool;
- (d) linearly moving the rivet punch in a fluid-free manner;
- (e) clamping the automotive vehicle workpieces together adjacent a solid portion of the automotive vehicle workpieces to be attached;
- (f) pushing the self-piercing rivet into the solid portion of the automotive vehicle workpieces;
- (g) using the die to outwardly diverge a leading end of the self-piercing rivet during insertion of the self-piercing rivet into the automotive vehicle workpieces;
- (h) preventing the self-piercing rivet from completely piercing through a die side one of the automotive vehicle workpieces; and
- (i) sensing a real time value of the electric motor during riveting operation and automatically comparing the real time value to a desired, stored value.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKewed/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.